

**In the Claims**

Claims 1-15 (Cancelled).

16. (Previously presented) A method for aligning a spectacle lens comprising a machined first side and a second side, the second side of the spectacle lens is secured to a first holder by connecting material, the method comprising:

positioning the first holder relative an adapter part, the adapter part comprising an alignment reference and a marking, wherein the positioning comprises aligning the first holder relative the alignment reference; and

aligning said spectacle lens relative a second holder using the marking of the adapter part.

17. (Previously presented) The method as claimed in claim 16 further comprising:  
connecting said spectacle lens to said second holder;  
inserting said second holder in a retaining device; and  
removing said first holder, said connecting material and said adapter part from said spectacle lens.

18. (Previously presented) The method as claimed in claim 17 wherein the removing comprises removing said first holder together with the adapter part.

19. (Previously presented) The method as claimed in claim 16 wherein the positioning of said first holder comprises using a collet chuck.

20. (Previously presented) The method as claimed in claim 16 wherein said spectacle lens comprises an organic spectacle lens, and wherein said organic spectacle lens comprises an organic progressive lens.

21. (Currently amended) An adapter part for aligning spectacle lenses, the spectacle lenses having a machined first side and a second side, said second side is provided with a first holder, the adapter part comprising:

an alignment reference and a collet chuck configured to position said first holder relative said adapter part; and

markings configured to align said spectacle lenses relative other structures.

22. (Previously presented) The adapter part as claimed in claim 21 wherein said alignment reference comprises a transverse web.

Claim 23 (Cancelled).

24. (Previously presented) The adapter part according to claim 22 wherein said transverse web is arranged in a cavity in a side of the adapter part.

25. (Previously presented) The adapter part as claimed in claim 24 wherein said markings are provided on another side of the adapter part opposite the side with said cavity.

26. (New) An adapter part for aligning spectacle lenses, the adapter part comprising:

an alignment reference structure extending from a surface of the adapter part, the alignment reference structure configured to position a first holder relative the adapter part; and

markings configured to align said spectacle lenses relative other structures.

27. (New) The adapter part as claimed in claim 26 wherein said alignment reference structure comprises a transverse web.

28. (New) The adapter part according to claim 27 wherein said transverse web is arranged in a cavity in a side of the adapter part.